

ACCESSORIES



Counter weight box is available for GT models. Does not fit model GT-250HY.



Wide gauge wheels are fitted with long-wearing double bearings and flotation tires.



Rubber wearing strips, mounted under the cutting edges provide protection to hard surfaces (asphalt, concrete etc.)



A hydraulic toplink with attachment brackets is available for blade adjustment.



The snow wing is puts a finishing touch to snow removal. The wing creates an angle on the snow edge preventing the snow from sliding back down.



The side/end plate can be fitted both to the right and left hand side (blade height 60cm/23,6 in). Mounted with three bolts.

Technical data:	GT-210	GT-210 front	GT-250	GT-250 front	GT-250S	GT-250S front	GT-250HY
Working width	2,10 m / 7'	2,10 m / 7'	2,50 m / 8'2"	2,50 m / 8'2"	2,50 m / 8'2"	2,50 m / 8'2"	2,50 m / 8'2"
Blade height	60 cm / 23,6 in	60 cm / 23,6 in	60 cm / 23,6 in	60 cm / 23,6 in	60 cm / 23,6 in	60 cm / 23,6 in	60 cm / 23,6 in
Cutting edge reversible	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Wheels	Option	Option	Option	Option	Option	Option	Option
Offset adjustment	50 cm / 19,7 in	20 cm / 7,9 in	50 cm / 19,7 in	20 cm / 7,9 in	50 cm / 19,7 in	20 cm / 7,9 in	50 cm / 19,7 in
Blade rotation	360°	360° dismount	360°	360° dismount	360°	360° dismount	270°, hydraulic
Vertical blade adjustment	1 pos.	1 pos.	1 pos.	1 pos.	3 pos.	3 pos.	1 pos.
Horizontal blade adjustment	0° or 7°	0° or 7°	0° or 7°	0° or 7°	0° or 7°	0° or 7°	0° or 7°
Hydraulic blade adjustments	Option	-	Option	-	Option	-	Standard
3-point linkage pins	Cat. I/II	Cat. I/II	Cat. I/II	Cat. I/II	Cat. I/II	Cat. I/II	Cat. I/II
Weight/lbs excl. wheels	360 kg / 793 lbs	340 kg / 750 lbs	385 kg / 849 lbs	365 kg / 805 lbs	425 kg / 937 lbs	405 kg / 893 lbs	450 kg / 992 lbs



ALSO IN THE FRANSGÅRD SALES PROGRAM...



5 Snow blower models for front and rear mounting.



Back tip shovel: T-200 with rear board. T-220 with automatic dumping.



The biggest world wide range of multi function rakes: 9 models.



Since we are constantly innovating our designs we reserve the right to making any technical changes!

Producent:

Fransgård

Fransgård Maskinfabrik A/S
 Fredbjergvej 132 · DK-9640 Farsø
 Tel. +45 98 63 21 22 · Fax +45 98 63 18 65
 www.fransgard.dk



Fransgård Scraper Blade program



The oval top link hole allows level operation of the blade in difficult terrain.

2 lift arm hole positions offer a variety of blade angle positions.



Easy blade height adjustment of the gauge wheels in 25 mm/1 inch increments on each side of the blade.

Gauge wheel brackets are standard on all GT models.



Adjustable horizontal pitch angle up to 7 degrees on either side using lift arm hole positions.

Horizontal pitch angle may also be adjusted using the gauge wheel brackets.



Available in 4 different cutting edge configurations:

- Serrated / serrated
- Plain / serrated
- Plain / plain
- Rubber (see options)

The bolt-on, reversible cutting edges are made of special hardened steel.



Available in 12 different models



The GT-250HY includes a strong hydraulic cylinder for rotating the blade as standard equipment. The blade can rotate 270°.



Three vertical blade adjustment positions are available on the GT-S model.



The front mounted versions have shorter beams making them more suitable for frontend 3 point hitch and loader applications.



The Front mounted versions are also suitable for mounting on the rear hitch of the tractor.

The blade must be dismantled from the hitch if a 180 degree rotation of the blade is required.



Offset adjustment
(without the use of any tools)

Left / right



10 adjustable blade positions
(without the use of any tools)

